



**21**

**Lumon Oy  
Kaitilankatu 11  
FI-45130 Kouvola  
LGR ETA-21/0677 of 09.08.2021**

**Balcony and Terrace glazing system without vertical frames**

- Lumon®Glazing Retractable Standard Lift Handle
- Lumon®Glazing Retractable Standard Handle
- Lumon®Glazing Retractable Strong Lift Handle
- Lumon®Glazing Retractable Strong Handle
- Lumon®Glazing Retractable Strong Low Threshold Handle

**Purpose of use: Balcony and Terrace glazing systems**

**Hygiene, health and the environment:**

Ventilation and dampness	Gaps 2-3 mm between glass panes assures ventilation, which reduces the risk of dampness or condensation.
--------------------------	--

**Safety and accessibility in use:** Resistance to wind load. EN 12211

	Max. Pane height [mm]	Max. Pane width [mm]	Thickness of glass [mm]	Max test pressure inward (+) Pa	Max test pressure outward (-) Pa	Pressure P3 estimated Pa
Lumon®Glazing Retractable Standard Lift Handle	2063	1000	6	700	700	700
	2363	1000	8	1000	900	900
	1663	1000	10	3500	4300	3500
	2863	650	10	1200	1200	1200
Lumon®Glazing Retractable Standard Handle	2063	1000	6	800	700	700
	2363	1000	8	900	1100	900
	1663	1000	10	3100	4100	3100
	2863	650	10	1100	1200	1100
Lumon®Glazing Retractable Strong Lift Handle	2360	1000	8	1200	1200	1200
	2860	1000	10	1200	1100	1100
	1660	1000	12	4100	5300	4100
	2860	800	12	1700	1700	1700
Lumon®Glazing Retractable Strong Handle	2360	1000	8	1100	1200	1100
	2860	1000	10	1200	1200	1200
	1660	1000	12	4000	5000	4000
	2860	800	12	1800	1800	1800
Lumon®Glazing Retractable Strong Low Threshold Handle	2377	665	8	1300	1300	1300
	2877	665	10	1200	1100	1100
	1677	665	12	5000	4800	4800
	2877	665	12	1700	1700	1700

**Safety in use:** Impact resistance of Lumon®Glazing Retractable. Impact from indoors and outdoors.

	Glass pane thickness [mm]	Drop height [mm]	Class according to EN 13049
Lumon®Glazing Retractable Standard Lift Handle	8	450	3
	10	450	3
Lumon®Glazing Retractable Standard Handle	8	200	1
	10	450	3
Lumon®Glazing Retractable Strong Lift Handle	8	450	3
	10	450	3
	12	900	4
Lumon®Glazing Retractable Strong Handle	8	200	1
	10	450	3
	12	450	3
Lumon®Glazing Retractable Strong Low Threshold Handle without lock in the middle	8	200	1
	10	450	3
	12	450	3
Lumon®Glazing Retractable Strong Low Threshold Handle with lock in the middle	8	200	1
	10	200	1
	12	200	1

### Durability

Plastic parts UV-ageing and heat testing 1000 h, ISO 4892-2	No influence on performance.
---	------------------------------

### Corrosion resistance

Metallic parts	At least moderate corrosion resistance in mild environments.
----------------	--

### Properties of panes

Resistance to racking	NPD
Resistance to static torsion	NPD

### Protection against noise

Airborne sound insulation	NPD
---------------------------	-----